THE HEATING CONTROL SYSTEM SELECTED FOR THE U.S. SUMMER OLYMPICS



ASSURES UNSURPASSED PERFORMANCE FROM YOUR SOLAR-HEATED POOL!

Efficient, economical, environmentally friendly solar energy, coupled with proven precision and reliability of the Helio–Matic® Control System – was the heating system selected for the pools at the U.S. Summer Olympic Games in Atlanta.

This same winning combination can insure that your pool's solar heating operates at peak efficiency – easily, automatically, and oh, so enjoyably!

Not only will your pool water be warm and comfortable every time you dip a toe, this Olympic-level system is designed to extend your enjoyment of the entire swimming season by providing warm water even under less than ideal weather conditions.

Proven in thousands of installations, both residential and commercial, Heliotrope's reputation

for and insistence on *quality*, down to the smallest system component, has resulted in unprecedented user satisfaction for over a quarter of a century.


Make the most of your pool's solar heating system. Make the choice of U.S. Olympic engineers –The Helio-Matic®Control System from Heliotrope, for years of unsurpassed swimming pleasure.

And no one is more deserving of the best than you. By choosing solar heating for your pool, you are showing your concerns for our earth's resources, now, and for generations to come. Thank you.

Heliotrope Pool

Among the reasons the Helio-Matic® Controller was chosen for the U.S. Summer Olympics was ease of operation.

Basically, it's as simple as setting a thermostat. Simply set the desired water temperature on the Helio-Matic® Electronic Controller. Two precision sensors, one for the pool water, and one simulating the solar collector, signal the controller when climate conditions are right for the water to be heated. If the water temperature is not above the desired setting, the controller opens the Flo-Verter® Valve, sending water through the solar collectors, gathering warmth and returning to the pool. When the desired temperature is reached, the controller automatically closes the operating valve.




The "Mind and Muscle" of the Olympic Control System:

- Color-coded wire terminals to match Flo-Verter[®] wire colors.
- Calibrated control knob for precise maximum temperature.
- Aluminum block sensor for collector simulation. Does not need to be mounted on the collectors.
- Lightning arc absorbers for sensors.
- HM 5000 model for pump control and/or valve plus pump.
- Extra UV protection enclosure for longer-lasting like-new appearance.
- Models also available for pool sweep delay protection and isolated relay contacts.


Flo-Verter® Valve

- Mounts in any position except upside-down.
- Twin o-rings on shaft to outlast single o-rings.
 - · Low-profile design, with two synchronous motors.
 - Uses either 12 or 24 VAC input without need for adjustment.
 - Water flows through curved and fluted diverter for less pressure drop. Equivalent to one 90° L.
 - Unibody valve and actuator require no assembly.
 - Actuator easily replaced.
 - Simple handle for manual control.
 - Non-positive seal, for freeze-protection draining. Positive seal also available.
 - Pre-wired with color-coded wires for fast and easy hook-up to controller.





WARRANTY Both the Helio-Matic® Controller and the Flo-Verter® Valve carry a ten year warranty. See warranty for details.



204 Greenfield Drive, Ste. E El Cajon, CA 92020 Phone 866-314-8400 Fax 866-314-8600

RSK OF ELECTRICAL SHOCK. OT POWER SOURCE BEFORE SERVICING.



